

DECLARATION OF PERFORMANCE

DoP number : N°DOP-DECOLISS-001

Unique identification code: DECOLISS

Intended use: Facing plaster mortar (CR)

Manufacturer: CHAUX DE SAINT-ASTIER
28 Bis Route de Montanceix
La Jarthe - 24110 SAINT-ASTIER

Assessment and verification of constancy of performance systems: Niveau 4

Harmonised standard: NF EN 998-1 : 2016

The manufacturer has carried out the determination of the product type based on initial type testing and factory production control according to system 4.

Declared performance:

Essential Characteristics	Performance	Harmonised technical specifications
Reaction to fire	Class A1	EN 998-1 : 2016
Compressive strength	CS I	
Water absorption by capillarity	W0	
Water vapour permeability (μ)	$\mu = 5/15$ (Tabulated value)	
Thermal conductivity (I10 sec)	$\lambda = 0,3$ (Tabulated value)	
Adhesion	$\geq 0,3$ N/mm ² - FP : A B C	
Durability	No testing standard	
Hazardous substances	FDS/SDS	

The performance of the product identified above complies with the declared performance.

In accordance with Regulation (EU) No. 305/2011, this Declaration of Performance is issued under the sole responsibility of the manufacturer mentioned above.

Signed for the manufacturer and on its behalf by:

The Technical Director
Laurent TEDESCHI

In Saint-Astier, on the 28/01/2025



CE	
07	
CHAUX DE SAINT-ASTIER	
La Jarthe - 24110 SAINT-ASTIER - France	
Facing plaster mortar (CR)	
N°DOP-DECOLISS-001	
EN 998-1 : 2016	
Reaction to fire	Class A1
Compressive strength	CS I
Water absorption by capillarity	W0
Water vapour permeability (μ)	$\mu = 5/15$ (Tabulated value)
Thermal conductivity (I10 sec)	$\lambda = 0,3$ (Tabulated value)
Adhesion	$\geq 0,3$ N/mm ² - FP : A B C
Durability	No testing standard
Hazardous substances	FDS/SDS