

DECLARATION OF PERFORMANCE

DoP number : **N°DOP-SANIMUR-001**

Unique identification code: **SANIMUR**

Intended use: **Sanitation coating mortar (R)**

Manufacturer: **CHAUX DE SAINT-ASTIER**
28 Bis Route de Montanceix
La Jarthe - 24110 SAINT-ASTIER

Assessment and verification of constancy of performance systems: Niveau 4

Harmonised standard: **NF EN 998-1 : 2016**

The manufacturer has carried out the determination of the product type based on initial type testing and factory production control according to system 4.

Declared performance:

Essential Characteristics	Performance	Harmonised technical specifications
Reaction to fire	Class A1	EN 998-1 : 2016
Compressive strength	CS II	
Water absorption by capillarity	$\geq 0,3 \text{ Kg/m}^2$ après 24h00	
Water vapour permeability (μ)	$\mu = 10$ (Measured value)	
Thermal conductivity (I10 sec)	$\lambda = 0,3$ (Tabulated value)	
Adhesion	$\geq 0,3 \text{ N/mm}^2$ - FP : A B C	
Durability	No testing standard	
Hazardous substances	FDS/SDS	

The performance of the product identified above complies with the declared performance.


In accordance with Regulation (EU) No. 305/2011, this Declaration of Performance is issued under the sole responsibility of the manufacturer mentioned above.

Signed for the manufacturer and on its behalf by:

The Technical Director
Laurent TEDESCHI

In Saint-Astier, on the 28/01/2025



	
05	
CHAUX DE SAINT-ASTIER	
La Jarthe - 24110 SAINT-ASTIER - France	
Sanitation coating mortar (R)	
N°DOP-SANIMUR-001	
EN 998-1 : 2016	
Reaction to fire	Class A1
Compressive strength	CS II
Water absorption by capillarity	$\geq 0,3 \text{ Kg/m}^2$ après 24h00
Water vapour permeability (μ)	$\mu = 10$ (Measured value)
Thermal conductivity (I10 sec)	$\lambda = 0,3$ (Tabulated value)
Adhesion	$\geq 0,3 \text{ N/mm}^2$ - FP : A B C
Durability	No testing standard
Hazardous substances	FDS/SDS