

DECLARATION OF PERFORMANCE

DoP number : N°DOP-NOVASKIN THERMO PLUS-001

Unique identification code: NOVASKIN THERMO PLUS

Intended use: Thermal insulation coating mortar (T)

Manufacturer: CHAUX DE SAINT-ASTIER
28 Bis Route de Montanceix
La Jarthe - 24110 SAINT-ASTIER

Assessment and verification of constancy of performance systems: Niveau 4

Harmonised standard: NF EN 998-1 : 2016

The manufacturer has carried out the determination of the product type based on initial type testing and factory production control according to system 4.

Declared performance:

| Essential Characteristics | Performance | Harmonised technical specifications |
|-------------------------------------|--|-------------------------------------|
| Reaction to fire | Class A1 | EN 998-1 : 2016 |
| Compressive strength | CS I | |
| Water absorption by capillarity | W1 | |
| Water vapour permeability (μ) | $\mu \leq 15$ | |
| Thermal conductivity (I10 sec) | $\lambda = 0,0793$ (Measured value) | |
| Adhesion | $\geq 0,3 \text{ N/mm}^2$ - FP : A B C | |
| Durability | No testing standard | |
| Hazardous substances | FDS/SDS | |


The performance of the product identified above complies with the declared performance.
In accordance with Regulation (EU) No. 305/2011, this Declaration of Performance is issued under the sole responsibility of the manufacturer mentioned above.

Signed for the manufacturer and on its behalf by:

The Technical Director
Laurent TEDESCHI

In Saint-Astier, on the 28/01/2025



| | |
|---|--|
|  | |
| 23 | |
| CHAUX DE SAINT-ASTIER La Jarthe - 24110 SAINT-ASTIER - France | |
| Thermal insulation coating mortar (T) | |
| N°DOP-NOVASKIN THERMO PLUS-001 | |
| EN 998-1 : 2016 | |
| Reaction to fire | Class A1 |
| Compressive strength | CS I |
| Water absorption by capillarity | W1 |
| Water vapour permeability (μ) | $\mu \leq 15$ |
| Thermal conductivity (I10 sec) | $\lambda = 0,0793$ (Measured value) |
| Adhesion | $\geq 0,3 \text{ N/mm}^2$ - FP : A B C |
| Durability | No testing standard |
| Hazardous substances | FDS/SDS |