

## DECLARATION OF PERFORMANCE

**DoP number :** N°DOP-KALAMUA OC-001

**Unique identification code:** KALAMUA OC

**Intended use:** Single-layer plaster mortar (OC)

**Manufacturer:** CHAUX DE SAINT-ASTIER  
28 Bis Route de Montanceix  
La Jarthe - 24110 SAINT-ASTIER

**Assessment and verification of constancy of performance systems:** Niveau 4

**Harmonised standard:** NF EN 998-1 : 2016

The manufacturer has carried out the determination of the product type based on initial type testing and factory production control according to system 4.

**Declared performance:**

Essential Characteristics	Performance	Harmonised technical specifications
Reaction to fire	Classe A1	EN 998-1 : 2016
Compressive strength	CS I	
Water absorption by capillarity	Wc2 Measured value 0,05 kg/m <sup>2</sup> min <sup>0,5</sup>	
Water vapour permeability (μ)	μ = 6	
Thermal conductivity (I10 sec)	λ = 0,76 (Tabulated value)	
Adhesion after conditioning cycles	≥ 0,3 N/mm <sup>2</sup> - FP : A B C	
Water permeability after conditioning cycles	≤ 0,15 ml/cm <sup>2</sup>	
Durability	No testing standard	
Hazardous substances	FDS/SDS	

The performance of the product identified above complies with the declared performance.  
In accordance with Regulation (EU) No. 305/2011, this Declaration of Performance is issued under the sole responsibility of the manufacturer mentioned above.

**Signed for the manufacturer and on its behalf by:**

**The Technical Director**  
Laurent TEDESCHI



In Saint-Astier, on the 28/01/2026